

Features & Functions

Vu+	Ultimo	Duo	Duo²	Uno	Solo	Solo²	Solo^{SE}	SoloSEV2	Solo4K	Zero
CPU Type	MIPS	MIPS	MIPS	MIPS	MIPS	MIPS	MIPS	MIPS	ARM	MIPS
CPU (MHz)	2x400	400	2x1300	2x400	333*	2x1300	2x1300	2x1300	2x1500	742
RAM (MB)	512	384	2048	512	256	1024	1024	1024	2048	512
Flash (MB)	1024	128	1024	128	128	256	256	512	4096	256
Flash type	(NAND)	(NAND)	(NAND)	(NAND)	(NAND)	(NAND)	(NAND)	(NAND)	eMMC	(NAND)
DVB	3 X P&P (S2/C/T)	2 X S2	2 X S2/C/T2 Up to 4 tuners supported	1 X (S2/C/T)	1 X S2	2 X S2	1 X S2/C/T/T2	1 X S2/C/T/T2	2 x Fixed Dual FBC 1 x Dual S2/C/T/T2	1 X (S2)
HDTV	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
3D TV	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
PIP	Yes	Yes	Yes	same TP	No	Yes/HD	Yes	Yes	Yes	No
Common Interface	2	2	2	2	2	1	1	1	1	No
Smart card	2	2	2	2	1	2	1	1	2	1
USB	3 x 2.0	3 x 2.0	3 x 2.0	3 x 2.0	2 x 2.0	3 x 2.0	2 x 2.0	2 x 2.0	2 x 3.0 1 x 2.0	2 X 2.0
RS232	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
LAN (Mbit/s)	100 + 300Mbps USB-WIFI	100	Gigabit + WiFi 802.11n(up to 300Mbps)	100	100	Gigabit	100	100	Gigabit	100
HDD	2.5/3.5 in	3.5 in	2.5/3.5 in	2.5/3.5 in	No	2.5 in	No	No	Detachable 2.5"	No
ATA	SATA II	SATA II	SATA III	SATA II	No	SATA III	No	No	SATA III	No
eSATA	Yes	Yes	Yes	Yes	No	No	Yes	Yes	No	No
SCART	1	2	1	1	1	1	No	No	No	No
HDMI	1	1	1	1	1	1	1	1	1 (2.0)	1
Display	graphical VFD	VFD	3.2" TFT LCD (262,000 Color/16 bit)	VFD	No	VFD	Status LED	Status LED	3.5" TFT LCD (262,000/18bit)	Status LED
Other connectors	1 x YPrPb	1 x YPrPb	Digital Audio:S/ PDIF, Analogue Audio:Right & Left (Cinch x 2), Analogue Video: Component Video (YPbPr), Composite Video (Cinch x 1)		1 x YPrPb		Digital Audio : S/ PDIF, Analogue Audio : Right & Left(Cinch x 2) Composite Video (Cinch x 1)	Digital Audio : S/ PDIF, Analogue Audio : Right & Left(Cinch x 2) Composite Video (Cinch x 1)	Digital Audio: S/ PDIF	Composite Video & Analog Audio (Stereo Jack X 1)