



TECHNISTAR S6 Int. Edt.

HDTV digital satellite receiver with USB-PVR function

EAN	Item no.	Colour
4019588647176	0006/4717	black

CONNECTIONS	LNB	In operation: 4.8 W without LNB
HDMI (out): 1	Vertical power supply: 14 V	Standby: < 0,3 W
USB: 1 (USB 2.0)	Horizontal power supply: 18 V	POWER SUPPLY
Common Interface Plus (CI+): Yes	LNB modulation: 22 kHz	Nominal voltage: 230 V
Smartcard reader: Yes	LNB power supply: 400 mA	Frequency: 50 Hz
Digital electric audio output: Yes	DiSEqC: 1.0 / 1.2	Mains adapter: external DC 12V/2A
audio/video output analog (3.5 mm jack): Yes TechniSat specific adapter set necessary, available at 0000/3649	Single Cable Solution (SatCR): SCR1 = EN50494, SCR2 = EN50607	SUPPORTED FORMATS & CODECS
Ethernet 10/100 (RJ-45): Yes	MULTIMEDIA	Audio-Formats: MP3, WAV, AAC, FLAC, MP2, OGG, DDAC3, AIFF
F socket: Yes	Media Player: Yes	Picture-Formats: JPEG, BMP, GIF, PNG, TIFF
DECODER	DVR function: USB	Video-Codecs: MPEG-4, MPEG-2, H.264
Video decoder: MPEG-2 MP@HL/ML, H.264/MPEG-4 AVC	Timeshift: Yes	Video-Formats: MP4, M4V, MKV, MOV, MPG, TS, TS4, Xvid, M2TS, AVI, ASF
Audio decoder: MPEG-1 & MPEG-2 Layer I, II, III	Recordings edition function: Yes	TECHNISAT CONNECT
DECRYPTION SYSTEM	Recordings folder management: Yes	Control: Yes
Conax: Yes	OTHER FEATURES	SFI: Yes
CI+: Yes (v1.3)	Total programme memory: 9999	TUNER
DISPLAY	Regional channel selection: Yes	Tuner type: DigitalSat
Type: 7 segment, 4 digits, white	Sleep timer: Yes	DVB-S tuner: 1
ENVIRONMENT	Clock: Yes	Reception on: HD-TV, SD-TV, DVB radio
Ambient temperature: 5 ... 35 °C	Teletext: Yes	Demultiplexing: according ISO 13818-1
Humidity: 10 ... 75 %	Page memory: 1000	TUNER - SAT
Storage temperature: -20 ... 60 °C	Teletext subtitles: Yes	Reception range: 950 ... 2150 MHz
HOTEL MODE	Internet radio: Yes	Viterbi rates: 1/2, 2/3, 3/4, 5/6, 7/8
Protected access to hotel mode: Yes	OSD languages: Danish, German, English, French, Greek, Italian, Dutch, Norwegian, Polish, Portuguese, Russian, Swedish, Spanish, Czech, Turkish, Hungarian	DVB-S: QPSK
Customisable start screen: Yes	PICTURE FUNCTIONS	DVB-S: 2 ... 45 Mbaud
Lockable volume: Yes	Freeze frame: Yes	DVB-S2: 8PSK - QPSK
Menu locking: Yes	PICTURE-FORMATS	DVB-S2: 2 ... 45 Mbaud
Control panel lock: Yes	Picture-Formats: 576i, 576p, 720p, 1080i, 1080p	FEC: Viterbi and Reed-Solomon
Integrated LED clock: Yes	POWER CONSUMPTION	SCOPE OF DELIVERY
Selectable start source: Yes		
Selectable start channel: Yes		

KEYFEATURES

"SiehFern INFO" (SFI)	DVRready	Network interface
ISIPRO	Timeshift	Editing function
TechniMatic	Perfect Recording	TechniRouter-ready
AutoInstall	Pay TV ready	
TechniFamily	Universal Plug And Play (UPnP)	